

**PRODUCT DATA SHEET**  
**PRODUCT CODE: P700 - PLASTER KEY****Description**

Plasterkey is a universal water based bonding aid

**Principal uses**

Plasterkey has been designed specifically for use in the building industry to bond sand/cement plaster and gypsum plaster to smooth surfaces.

**Advantages**

- Improves non-structural bond of cement & gypsum plasters
- No more hacking and chipping of smooth surfaces
- Bonds to sound PVA surfaces
- Easy to use

**Surface preparation**

Surfaces should be free of loose particles, scaling or flaking material. Wire brush & rinse the surface if necessary

**Application**

Soffits and vertical surfaces - coat the prepared surfaces with a scratch coat consisting of 2 parts river sand, 1 part cement and Plasterkey after dust etc. has been removed. The scratch coat can be applied either by throwing it onto the surface with a trowel or block brush. Alternatively use a tyraline machine. Allow the scratch coat to dry and then plaster in the usual manner.

Where gypsum based plaster is used, apply the Plasterkey to the prepared surface and plaster straight onto the wet Plasterkey finishing off in a single operation.

Plasterkey can be added to a sand / cement plaster mix (10 % of water content) to obtain a stronger bond. Plasterkey can be applied by brush or roller.

**Coverage**

Coverage is  $\pm$  10 square metres per litre

**Packaging**

Plasterkey is available in 210L, 25L, 10L and 5L Containers

**Safety & handling**

Use gloves and eye protection at all times. Should the product come into contact with eyes, wash immediately and seek medical advice

**Shelf Life & Storage**

12 months when stored in a cool dry place, failure to comply with these recommendations will result in a reduction in shelf life

Note: The information and specifications provided is to the best of our knowledge. The technical data contained herein are true and accurate at the date of issue and are subject to change without prior notice. No guarantee of accuracy is given or implied. We guarantee our products to conform to ASHAK Construction Chemicals quality control. We cannot be held responsible or liable, directly or indirectly for the use of our products, coverage, performance or injury resulting from use, as we have no control over the method of application used or site conditions. For further technical and method statements, contact our Technical representatives.